

SQ 058


BECK-CRESPEL
Sefer la performance • Tightening up on performance

MAN FERROSTAAL PIPING SUPPLY GMBH

LE 28/02/2006

REF. 4500062573

CERTIFICAT D'ESSAIS/TEST CERTIFICATE EN 10204.3.1 NR 05308/34 - 1414/356

ANALYSE CHIMIQUE/CHEMICAL ANALYSIS

POSTE ITEM NO	DESCRIPT. & DIAM	COULEE HEAT NO											R T.S MPA	E Y.S. MPA	A% E%	Z% R%	RESILIENCE IMPACT VALUES	REV. TEMP T.C°	DURETE DE LIVRAISON DELIVERY HARDNESS	DUR. APRES T.T. 24H EPRUVE HARD. AFTER PROOF 24H H-T	CHARGE EPRUVE LOAD
			C.	MN.	P.	S.	SI	NI	CR	MO	V.	T.	AL	B.							

1 | TF:1 1/4 " | K20692 | .385 | .820 | .004 | .006 | .260 |

TF: A193-B7

1.020 | .220 |

Standard ASTM 04b

992 | 914 | 19.00 | 60.00 |

Marks : BC B7

725 | 294/296HB |

Delivery State: QUENCHED & TEMPERED

2 | TF:1 1/8 " | 321811 | .418 | .840 | .009 | .003 | .290 |

1.050 | .220 |